

200 Series

Digital Indicator



NTEP CC 00-065



200 - LCD Display



200E - LED Display

- **Divisions**— NTEP approved for 5,000 divisions
- **Displays**— Up to 50,000 graduations
- **Enclosure**— ABS NEMA 12
- **Load Cells**— Drives up to four 350Ω load cells

VALUE IN
WEIGHING

200 Series Digital Indicator

Features

- Serial Port**— Full duplex RS-232 serial port
- Digital Calibration**— Full front panel calibration
- Construction**— Stainless steel swivel stand
- Power Requirements**— Operates on AC adapter
- S200**— LCD display
- S200E**— LED display

Specifications

- Load Cell Excitation**— +5 VDC
- Load Cell Current**— Drives up to four 350 Ω load cells
- Analog Signal Input Range**— ± 3.125 mV/V max
- Analog Sensitivity**— 0.3 μ V/grad, minimum
0.6 μ V/grad recommended
minimum for legal-for-trade
- A/D Conversion Rate**— 10 Hz
- A/D Resolution**— Up to 200,000 internal counts
- Display**— 0.6", 6 digit
- Display Resolution**— Up to 50,000 external grads,
selectable
- Keyboard Functions**— Units, Zero, Net/Gross, Tare, Print
- Annunciators**— Gross, Net, kg, lb, Center of Zero, Stable,
Tare, Negative, PCS
- Serial Port**— Full duplex RS-232 format
- Power Requirement**—
 - LED, 9 VDC, 500 mA wall adapter (included)
 - LCD, 9 VDC, 500 mA wall adapter (included)
- Indicator Dimensions**— 3.2" x 6.8" x 2.3"
- Operating Temp**— -10° C to 40° C (14° F to 104° F)
- Certifications**— NTEP, CC #00-065



a division of Avery Weigh-Tronix, LLC

Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@salterbrecknell.com
www.salterbrecknell.com

